

TECHNICAL DATA SHEET

NASA Super Sonic Grease-Non Drop

SECTION 1: Product Description & Advantages

1.1 Product Description

NASA Super Sonic Non-Drop Grease is a non-soap based grease for plain and rolling bearings operating at high temperatures. It is a multi-purpose grease containing anti-corrosion and EP additives and is suitable for most conditions especially at elevated temperatures. This grease gives excellent service life at temperatures in excess of 160°C, provided the re-lubrication period is suitably adjusted. It is mostly used for fans, plumber blades, underground mining, plastic injection molders, and bearings.

1.2 Advantages

1. Protects at High Temperatures.
2. Non-melting.
3. Good sealing properties.
4. Softening resistance.
5. Good EP properties.
6. Reduces maintenance.
7. Leak-Resistant.

SECTION 2: Typical Data

Property	Result
Composition	Base Oil, Polymer & Ep and Antirust Additive
Appearance	Smooth Natural Golden Color
pH	6.00
Odor	Natural Lubricant
Density at 25 °C, g/ml	0.840
Dropping Point	Non Drop
Viscosity, mPa·s	8500



DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself to the suitability of such information for his own particular use.