

TECHNICAL DATA SHEET

NASA Liquid Grease-Grease Spray

SECTION 1: Product Description & Advantages

1.1 Product Description

NASA Liquid Grease Spray is a special protective high temperature grease ideal for metal-to-metal applications that require heavy-duty lubrication and greasing protection against rust and corrosion.

It can be used in door gates, hinges, home appliances, arms and machinery, bearing, accelerators, clutch, levers, gears & battery terminals. Greasing in electronic components, wire, hinges, and spark plugs and other electronic contacts to protect against moisture and water. It creates a thick protective coating layer that does not runoff easily.

1.2 Advantages

1. Protects against rust and corrosion, sealing out moisture, and prolonging the life of joints.
2. This Multi-purpose Liquid Grease spray is the solution for all of your lubricating and greasing need.

1.3 Precautions

1. Before use disconnect electrical connection.
2. Attach extension tube to the sprayer.
3. Extremely flammable.
4. Keep it away from heat and do not expose to the temperature exceeding 35°C.
5. Keep it away from the children.

SECTION 2: Typical Data

Property	Result
Composition	Base Oil, polymer and EP additive
Appearance	Smooth natural white color
pH	6.00
odor	Natural lubricant
Density at 25 °C, g/ml	0.782
Dropping point	Non Drop
Viscosity, mPa-s	3900



DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself to the suitability of such information for his own particular use.