NASA® CHEMICALS (PVT.) LTD.

TECHNICAL DATA SHEET
NASA Radiator Cleaner

SECTION 1: Product Description & Advantages

1.1 Product Description

NASA Radiator Cleaner is very effective in cleaning the radiators of Automobiles and Generators. It is especially designed to clean the cooling system quickly and effectively, preventing burns, cracks and corrosion in the radiator system. It clears blocked water channels that can cause overheating while removing rust and sludge.

1.2 Usage of Recommendation

1. 1 Ltr for small cars (800cc to 1800 cc). 2 Ltrs for vans and light truck (2000 cc to 4200 cc).
2. For Heavy-duty vehicles and generators use 50% water and 50% **NASA Radiator Cleaner**.

1.3 Direction of use

3. Before use, drain and flush all water/coolant from radiator.
4. Fill the **NASA Radiator Cleaner** as per the above recommendation and fill the radiator with water.
5. Start the engine at a normal speed for 5 minutes.
6. Open the drain cock and drain out all the **Radiator Cleaner** from the radiator and run clear water in good quality to clean and clear the radiator from the radiator cleaner and any other particles.
7. For long-lasting results, fill the radiator with **NASA Anti-freeze Coolant** after cleaning the Radiator.

SECTION 2: Typical Data

Property	Result
Composition	Acid Base Chemical
Appearance	Clear
pH	9.00
Odor	Characteristic
Specific Gravity at 25 °C	1.030
Water Solubility	Soluble
Equilibrium Boiling point, °C	100
Viscosity at 40 °C, cst	0.875



DISCLAIMER

This information relates only to the specific material designated and may not be applicable when the material is used in combination with other materials or in any particular process. The information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated.

However, no warranty, guarantee, or representation, expressed or implied, is made regarding its accuracy, reliability, or completeness. It is the user's responsibility to determine the suitability of this information for their specific application or use. The company shall not be held liable for any damages resulting from improper handling, storage, or use of the product.